

SAFETY DATA SHEET

1. Identification

Product identifier Engine Brite Heavy Duty Engine Degreaser

Other means of identification

SDS number EB1

Part No. EB1, EB1/6
Tariff code 3814.00.5090

Recommended use Engine Degreaser

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name

Blaster LLC

Address

8500 Sweet Valley Drive Valley

Telephone View, Ohio 44125 - USA

T(216)901-5800

Website F (216)901-5801
E-mail www.blastercorp.com

Emergency phone number

Chemtrec (800) 424-9300

2. Hazard(s) identification

 Physical hazards
 Flammable aerosols
 Category 1

 Health hazards
 Acute toxicity, oral
 Category 4

 Skin corrosion/irritation
 Category 2

Serious eye damage/eye irritation Category 2A Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Harmful if swallowed. May be fatal if swallowed and enters airways.

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated

Category 2

exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective

gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical

advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information NOTE: This product is a consumer product and is labeled in accordance with the US Consumer

Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the

workplace.

3. Composition/information on ingredients

Mixtures

Chemical name	emical name Common name and synonyms		%	
Petroleum Distillate Aliphatic		68476-34-6	60 - < 70	
Kerosene		8008-20-6	20 - < 30	
C9-15 Heavy Aromatic Hydrocarbons		64742-94-5	3 - < 5	
Alkanes C10-20, Branched And Linear		928771-01-1	1 - < 3	
Carbon Dioxide		124-38-9	1 - < 3	
Poly(oxyethylene) Sorbitol Hexaoleate		57171-56-9	1 - < 3	
Tert-butylbenzene		98-06-6	1 - < 3	
Naphthalene		91-20-3	< 1	
Other components below reportable le	evels		3 - < 5	

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media

Alcohol resistant foam. Dry powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Material name: Engine Brite Heavy Duty Engine Degreaser

EB1, EB1/6 Version #: 12 Revision date: 02-21-2023 Issue date: 05-20-2015

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	
C9-15 Heavy Aromatic Hydrocarbons (CAS 64742-94-5)	PEL	400 mg/m3	
		100 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
Naphthalene (CAS 91-20-3)	PEL	50 mg/m3	

Components	Туре	Value	
		10 ppm	
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
C9-15 Heavy Aromatic Hydrocarbons (CAS 64742-94-5)	TWA	200 mg/m3	Non-aerosol.
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Kerosene (CAS 8008-20-6)	TWA	200 mg/m3	Non-aerosol.
Naphthalene (CAS 91-20-3)	TWA	10 ppm	
Petroleum Distillate Aliphatic (CAS 68476-34-6)	TWA	100 mg/m3	Inhalable fraction and vapor.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Kerosene (CAS 8008-20-6)	TWA	100 mg/m3	
Naphthalene (CAS 91-20-3)	STEL	75 mg/m3	
		15 ppm	
	TWA	50 mg/m3	
		10 ppm	
ogical limit values	No biological exposure limits r	noted for the ingredient(s).	
osure guidelines			
US - California OELs: Skin	designation		
Naphthalene (CAS 91-20 US ACGIH Threshold Limit		Can be absorbed through the skin.	
	ydrocarbons (CAS 64742-94-5) -3)	Can be absorbed through the skin. Can be absorbed through the skin. Can be absorbed through the skin. Can be absorbed through the skin.	

should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

•	, .	•		
Eye/face protection	Chemical	respirator with	organic vapor	cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. Chemical respirator with

organic vapor cartridge and full facepiece if threshold limits are exceeded.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear.
Physical state Liquid.
Form Aerosol.
Color Red

Odor Diesel Fuel odor
Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

330 °F (165.56 °C) estimated

range

Flash point 136.0 °F (57.8 °C) Tag Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 % estimated

(%)

Flammability limit - upper

5 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 2.66645 hPa estimated

Vapor densityNot available.Relative density0.834 g/cm3

Solubility(ies)

Solubility (water) 0.1

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature 500 °F (260 °C) estimated

Decomposition temperatureNot available.ViscosityNot available.Other informationNone known.Density7.01 lbs/galExplosive propertiesNot explosive.

Flammability (flash back) No

Flammability class Combustible II estimated

Heat of combustion (NFPA 3

30B)

39.8 kJ/g

Oxidizing properties Not oxidizing.

Percent volatile 0.98 % estimated

Specific gravity 0.84

VOC 14.69 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or

vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components Species Test Results

C9-15 Heavy Aromatic Hydrocarbons (CAS 64742-94-5)

<u>Acute</u>

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat < 5.8 mg/l, 4 Hours

Oral

LD50 Rat < 5000 mg/kg

> 25 ml/kg

Kerosene (CAS 8008-20-6)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg, 24 Hours

Inhalation

Vapor

LC50 Rat > 0.1 mg/l, 8 Hours

Oral

LD50 Rat > 5000 mg/kg

Naphthalene (CAS 91-20-3)

Acute

Dermal

LD50 Rabbit > 2 g/kg

Oral

LD50 Rat 490 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Naphthalene (CAS 91-20-3) 2B Possibly carcinogenic to humans.

Petroleum Distillate Aliphatic (CAS 68476-34-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Naphthalene (CAS 91-20-3) Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components **Test Results**

C9-15 Heavy Aromatic Hydrocarbons (CAS 64742-94-5)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 2.7 - 5.1 mg/l, 48 hours Rainbow trout, donaldson trout Fish LC50 8.8 mg/l, 96 hours

(Oncorhynchus mykiss)

8.8 mg/l, 96 hours

Naphthalene (CAS 91-20-3)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1.09 - 3.4 mg/l, 48 hours LC50 Pink salmon (Oncorhynchus gorbuscha) 1.11 - 1.68 mg/l, 96 hours Fish

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Naphthalene 3.3 Tert-butylbenzene 4.11

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions**

> under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

D001: Waste Flammable material with a flash point <140 F Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950 UN proper shipping name

Aerosols, flammable, (each not exceeding 1 L capacity), Limited Quantity

Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) 2.1

Packing group Not available.

Environmental hazards

No Marine pollutant

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 306 Packaging exceptions Packaging non bulk None Packaging bulk None

IATA

UN1950 **UN** number

Aerosols, flammable, Limited Quantity **UN** proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk

Packing group Not available.

Environmental hazards No **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

AEROSOLS, Limited Quantity

Cargo aircraft only

Allowed with restrictions.

Not established.

IMDG

UN1950 **UN** number

UN proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk

Not available. Packing group


Environmental hazards

Marine pollutant No F-D, S-U **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Naphthalene (CAS 91-20-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Naphthalene	91-20-3	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Naphthalene (CAS 91-20-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Naphthalene, which are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

 Cumene (CAS 98-82-8)
 Listed: April 6, 2010

 Naphthalene (CAS 91-20-3)
 Listed: April 19, 2002

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Kerosene (CAS 8008-20-6) Naphthalene (CAS 91-20-3)

Petroleum Distillate Aliphatic (CAS 68476-34-6)

Tert-butylbenzene (CAS 98-06-6)

Volatile organic compounds (VOC) regulations

EPA

Compliant Consumer products (40 CFR 59, Subpt. C)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical	No

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) Nο Korea Existing Chemicals List (ECL) Νo New Zealand New Zealand Inventory Nο **Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

Taiwan Chemical Substance Inventory (TCSI) Taiwan No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

05-20-2015 Issue date **Revision date** 02-21-2023

Version # 12

HMIS® ratings Health: 3*

Flammability: 2 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 2 Instability: 0

NFPA ratings



Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

> information and belief at the date of its publication. The information given is designed only as a quidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Hazard(s) identification: Hazard statement **Revision information**

> Hazard(s) identification: Prevention Hazard(s) identification: Response Hazard(s) identification: GHS Symbols

Hazard(s) identification: Supplemental information

Accidental release measures: Methods and materials for containment and cleaning up

Accidental release measures: Environmental precautions Physical & Chemical Properties: Multiple Properties Stability and reactivity: Possibility of hazardous reactions

Ecological information: Ecotoxicity

Transport Information: Material Transportation Information

Transport information: General information

GHS: Classification

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).