



SAFETY DATA SHEET

M4814C

Page 1 of 11

Carburetor & Choke Cleaner

SDS Preparation Date (mm/dd/yyyy): 03/31/2023

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Carburetor & Choke Cleaner**

Product Code(s) : M4814C

Recommended use of the chemical and restrictions on use

: Carburetor choke and valve cleaner.
Restrictions on use: Not available.

Chemical family : Mixture of: Aromatic hydrocarbons; Ketones; Propellant; Alcohol

Manufacturer/Importer/Supplier/Distributor Information:

Company name Blaster LLC
Address 8500 Sweet Valley Drive
Valley View, Ohio 44125 - USA
Telephone (216)901-5800
(800)858-6605 (Canada)
Website www.blastercorp.com

Emergency phone number : Chemtrec (800) 424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear liquid, contained in a pressurized aerosol can. Hydrocarbon odour.

Most important hazards:

Extremely flammable aerosol. This material may be ignited by heat, sparks and direct flame. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time. Aspiration hazard. Can enter the lungs and cause damage. Irritating to eyes, respiratory system and skin. Inhalation may cause central nervous system depression. Possible cancer hazard - contains material which may cause cancer. Contains material which can cause birth defects based on animal data. Causes damage to organs. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS.

Toxic to aquatic life with long lasting effects. Avoid release to the environment. See Section 12 for more environmental information.

This product is packaged and sold as a consumer product. The Hazardous Products Act (HPA) does not apply to consumer products [Hazardous Products Act Section 12(j)]. The below WHMIS 2015 classification and labeling information is being provided for informational purposes.

This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Hazardous classification:

Flammable aerosol - Category 1
Gases under pressure - Liquefied gas
Skin corrosion/irritation - Category 2
Eye damage/irritation - Category 2A
Carcinogenicity - Category 2
Reproductive toxicant - Category 2
Specific target organ toxicity, single exposure - Category 1
Specific target organ toxicity, single exposure - Category 3 (Respiratory irritation; Narcotic effects)
Aspiration toxicity - Category 1

Label elements

Hazard pictogram(s)



Signal Word

DANGER!

SAFETY DATA SHEET

Hazard statement(s)

Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause respiratory irritation.
 May cause drowsiness and dizziness.
 Suspected of causing cancer.
 Suspected of damaging the unborn child.
 Causes damage to organs.

Precautionary statement(s)

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe mist or vapor.
 Wash hands and face thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/clothing and eye/face protection.

If exposed or concerned: Call a POISON CENTER or doctor/physician.
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
 IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.
 If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local regulation.

Other hazards*Other hazards which do not result in classification:*

Burning produces obnoxious and toxic fumes. May cause gastrointestinal irritation. Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights. Excessive overexposure could cause blood system effects (anemia).

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Xylene	Dimethylbenzene Methyltoluene Xylol	1330-20-7	30.0 - 60.0
Petroleum gases, liquefied	LPG	68476-85-7	10.0 - 30.0
Acetone	2-Propanone Methyl ketone	67-64-1	10.0 - 30.0
Ethylbenzene	Ethylbenzol Phenylethane	100-41-4	10.0 - 30.0
Methanol	Carbinol Methyl hydrate Methyl alcohol	67-56-1	1.0 - 5.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SAFETY DATA SHEET

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.
- Inhalation* : If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing is irregular or stopped, administer artificial respiration. Call a POISON CENTER or doctor/physician if you feel unwell.
- Skin contact* : IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: get medical advice/attention.

Most important symptoms and effects, both acute and delayed

- : May be an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.
- Causes skin irritation. Contact may cause redness, swelling and a painful sensation.
- Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.
- Suspected of causing cancer. Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing.
- Suspected of damaging the unborn child. Symptoms may include reduced fetal weight, delayed ossification and persistent behavioural effects.
- May cause respiratory irritation. May cause coughing and breathing difficulties.
- May cause drowsiness and dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.
- Causes damage to organs. Causes damage to the optic nerves (eyes) if swallowed.
- Affected person could experience a latent period of no symptoms, followed by blurred vision and possibly blindness.
- Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
- Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.
- Excessive overexposure could cause blood system effects (anemia).

Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Aspiration hazard if swallowed - can enter lungs and cause damage.
- Provide general supportive measures and treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

- Suitable extinguishing media* : Carbon dioxide (CO₂); Dry chemical; Alcohol resistant foam; Water fog.
- Unsuitable extinguishing media* : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Extremely flammable aerosol. This material may be ignited by heat, sparks and direct flame. This product is contained under pressure, and could explode when exposed to heat and flame. Vapours are heavier than air and may spread along floors. Product may float, and be re-ignited at the water's surface. Toxic fumes, gases or vapours may evolve on burning.

Hazardous combustion products

- : Carbon oxides; Aldehydes; Reactive hydrocarbons; acetic acid; Other unidentified organic compounds

Special protective equipment and precautions for firefighters

- Protective equipment for fire-fighters* : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

SAFETY DATA SHEET

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Shield personnel to protect from venting or rupturing containers. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. For spilled liquids: absorb spill with inert, non-combustible material such as sand, then place into suitable containers. Do not use combustible absorbents, such as sawdust. Pick up and transfer to properly labeled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.
Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective gloves/clothing and eye/face protection. Do not breathe mist or vapor. Do not ingest. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking. Do not spray on an open flame or other ignition source. Do not use on vehicles unless cool. Pressurized container: Do not pierce or burn, even after use. Keep away from incompatibles. Always replace cap after use. Wash thoroughly after handling. Empty containers retain residue (liquid and/or vapour) and can be dangerous.

Conditions for safe storage : Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Protect from sunlight. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Keep away from incompatibles.

Incompatible materials : Strong oxidizing agents; Reducing agents; Reactive metals; Strong acids

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Xylene	100 ppm	150 ppm	100 ppm (435 mg/m ³)	N/Av
Petroleum gases, liquefied	N/Av	N/Av	1000 ppm (1800 mg/m ³)	N/Av
Acetone	250 ppm	500 ppm	1000 ppm (2400 mg/m ³)	N/Av
Ethylbenzene	20 ppm	N/Av	100 ppm (435 mg/m ³)	N/Av
Methanol	200 ppm (skin)	250 ppm (skin)	200 ppm (260 mg/m ³)	N/Av

SAFETY DATA SHEET

Exposure controls

Ventilation and engineering measures

- : Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Skin protection

- : Wear protective gloves/clothing. Wear as appropriate: Nitrile rubber; Butyl rubber. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Wear resistant clothing and boots.

Eye / face protection

- : Wear eye/face protection. Chemical splash goggles are recommended. A full face shield may also be necessary.

Other protective equipment

- : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Do not breathe mist or vapor. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear liquid, contained in a pressurized aerosol can.

Odour : Hydrocarbon odour.

Odour threshold : N/Av

pH : N/Av

Melting/Freezing point : Melting point: N/Av
Freezing point: N/Av

Initial boiling point and boiling range

: N/Av

Flash point : < 11°C (51.8°F) (concentrate)

Flashpoint (Method) : Not known.

Evaporation rate (BuAe = 1) : N/Av

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

: N/Av

Upper flammable limit (% by vol.)

: N/Av

Oxidizing properties : No oxidizing properties.

Explosive properties : Aerosols are sensitive to mechanical impact. Closed containers are contained under pressure and may explode if exposed to excess heat for a prolonged period of time.

Vapour pressure : N/Av

Vapour density : N/Av

Relative density / Specific gravity

: Relative density: 840 kg/m³ @ 15°C (59°F)
Specific Gravity: 0.84 @ 15°C (59°F)

Solubility in water : Negligible.

Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av

Decomposition temperature : N/Av

Viscosity : < 14 cSt @ 40°C (104°F) (concentrate)

Volatiles (% by weight) : 81%

SAFETY DATA SHEET

Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Av

Flame projection length : > 15 cm, < 70 cm (> 5.91, < 27.6")

Other physical/chemical comments

: Flashback Observed: NO
Chemical heat of combustion: N/Av

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.

Chemical stability : Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

: Hazardous polymerization does not occur. No dangerous reaction known under conditions of normal use.

Conditions to avoid

: Direct sources of heat. Keep away from direct sunlight. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials.

Incompatible materials

: Strong oxidizing agents; Reducing agents; Reactive metals; Strong acids

Hazardous decomposition products

: Not available.
In the event of fire: Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption

: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause respiratory irritation. May cause coughing and breathing difficulties. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache). Affected person could experience a latent period of no symptoms, followed by blurred vision and possibly blindness. Aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Sign and symptoms skin

: Causes skin irritation. Contact may cause redness, swelling and a painful sensation. May be absorbed through the skin.

Sign and symptoms eyes

: Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects

: Repeated exposure may cause skin dryness or cracking.
Prolonged overexposure may cause slight liver and kidney effects, such as increased organ weights.
Excessive overexposure could cause blood system effects (anemia).

Mutagenicity

: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

SAFETY DATA SHEET

Carcinogenicity : This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Carcinogenicity - Category 2. Suspected of causing cancer. Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3). Symptoms may include persistent coughing, shortness of breath, coughing up blood and wheezing.

Reproductive effects & Teratogenicity

: This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Reproductive toxicant - Category 2. Suspected of damaging the unborn child. This product contains Xylene. Xylene may cause fetotoxic effects (e.g. reduced fetal weight, delayed ossification, behavioral effects) at doses which are not maternally toxic, based on animal data. Contains Methanol. Methanol may cause fetotoxic and teratogenic effects at doses which are not maternally toxic, based on animal data. Symptoms may include reduced fetal weight, delayed ossification and persistent behavioural effects.

Sensitization to material : No data available to indicate product or components may be respiratory sensitizers. No data available to indicate product or components may be skin sensitizers.

Specific target organ effects : This material is classified as hazardous under Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Specific target organ toxicity, single exposure - Category 1. Causes damage to organs. Contains: Methanol. Causes damage to the optic nerves (eyes) if swallowed. Specific target organ toxicity, single exposure - Category 3. May cause drowsiness and dizziness. May cause respiratory irritation.

According to the classification criteria of Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause specific target organ toxicity (STOT) through repeated exposures.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

: None reported by the manufacturer.

Toxicological data

: Not classified for acute toxicity based on available data. No data is available on the product itself.

The calculated ATE values for this mixture are:

ATE oral = 2370 mg/kg

ATE dermal = 13,100 mg/kg

ATE inhalation (vapours) = 21.6 mg/L/4H

See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC₅₀ (4hr)</u> <u>inh, rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Xylene	6350 ppm (27.6 mg/L) (vapours)	3253 mg/kg	12 180 mg/kg
Petroleum gases, liquefied	276 000 ppm (Read-across)	N/Ap (gas)	N/Ap (gas)
Acetone	30 000 ppm (71 mg/L) (vapour)	5800 mg/kg	> 15 800 mg/kg
Ethylbenzene	4000 ppm (17.4 mg/L) (vapour)	3500 mg/kg	15 380 mg/kg
Methanol	> 5000 ppm/6H (4.1 mg/L/4H (vapour)	5628 mg/kg (rat) The estimated human lethal dose is: 300 - 1000 mg/kg	> 393 mg/kg (Monkey) 15 800 mg/kg (rabbit)

Other important toxicological hazards

: None reported by the manufacturer.

SAFETY DATA SHEET

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : Toxic to aquatic life with long lasting effects. No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. The product contains the following substances which are hazardous for the environment: Xylene.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	CAS No	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Xylene	1330-20-7	8.2 mg/L (Rainbow trout)	N/Av	None.
Petroleum gases, liquefied	68476-85-7	N/Ap	N/Ap	N/Ap
Acetone	67-64-1	6210 mg/L (Fathead minnow)	N/Av	None.
Ethylbenzene	100-41-4	4.2 mg/L (Rainbow trout)	1.13 mg/L (30 days)	None.
Methanol	67-56-1	15 400 mg/L (Bluegill sunfish)	446.7 mg/L/28-day (Fathead minnow) (QSAR)	None.

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Xylene	1330-20-7	3.2 - 9.56 mg/L (Daphnia magna)	N/Av	None.
Petroleum gases, liquefied	68476-85-7	N/Ap	N/Ap	N/Ap
Acetone	67-64-1	15 800 mg/L (Daphnia magna)	1660 mg/L	None.
Ethylbenzene	100-41-4	1.81 mg/L (Daphnia magna)	N/Av	None.
Methanol	67-56-1	> 10 000 mg/L (Daphnia magna)	208 mg/L (QSAR)	None.

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Xylene	1330-20-7	3.2 - 4.9 mg/L/72hr (Green algae)	N/Av	None.
Petroleum gases, liquefied	68476-85-7	N/Ap	N/Ap	N/Ap
Acetone	67-64-1	7000 mg/L/96hr (Green algae)	N/Av	None.
Ethylbenzene	100-41-4	3.6 mg/L/96hr (Green algae)	3.4 mg/L/96hr	None.
Methanol	67-56-1	22 000 mg/L/96hr (Green algae)	N/Av	None.

Persistence and degradability

: The product itself has not been tested.
The following ingredients are considered to be readily biodegradable: Acetone; Methanol.
Contains the following chemicals which are considered to be inherently biodegradable: Xylene; Ethylbenzene.

SAFETY DATA SHEET

Bioaccumulation potential : The product itself has not been tested. See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Xylene (CAS 1330-20-7)	3.12 - 3.2	50 - 58
Petroleum gases, liquefied (CAS 68476-85-7)	2.89 (Read-across)	33 (Read-across)
Acetone (CAS 67-64-1)	0.24	0.65 (Fish)
Ethylbenzene (CAS 100-41-4)	3.15	1.1 - 1.5
Methanol (CAS 67-56-1)	- 0.82 to - 0.64	< 10 (common carp)

Mobility in soil : The product itself has not been tested.

Other Adverse Environmental effects

: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.


SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice. Do not puncture or incinerate containers. Pressurized container: Do not pierce or burn, even after use. Refer to protective measures listed in sections 7 and 8. This material and its container must be disposed of in a safe way.

Empty containers retain residue and can be dangerous. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal : Dispose of in accordance with federal, provincial and local hazardous waste laws.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1950	AEROSOLS	2.1	None	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass. Under the TDG, refer to Section 1.17 for additional exemption requirements, if shipping under this exemption.				

Special precautions for user : Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards : This product meets the criteria for an environmentally hazardous material according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:

- Xylene (Part 1: Group A; Part 5: Isomer Groups);
- Ethylbenzene (Part 1, Group A Substance);
- Methanol (Part 1, Group A Substance; Part 5: Individual Substances)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

SAFETY DATA SHEET

US Federal Information:

TSCA: All listed ingredients appear on the Toxic Substances Control Act (TSCA) inventory.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	<u>CAS #</u>	<u>European EINECS</u>	<u>Australia AICS</u>	<u>Philippines PICCS</u>	<u>Japan ENCS</u>	<u>Korea KECI/KECL</u>	<u>China IECSC</u>	<u>New Zealand IOC</u>
Xylene	1330-20-7	215-535-7	Present	Present	(3)-60; (3)-3	KE-35427	Present	HSR000983
Petroleum gases, liquefied	68476-85-7	270-704-2	Present	Present	(9)-1697	KE-28191	Present	HSR001009
Acetone	67-64-1	200-662-2	Present	Present	(2)-542	KE-29367	Present	HSR001070
Ethylbenzene	100-41-4	202-849-4	Present	Present	(3)-60; (3)-28	KE-13532	Present	HSR001151
Methanol	67-56-1	200-659-6	Present	Present	(2)-201	KE-23193	Present	HSR001186

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
 AICS: Australian Inventory of Chemical Substances
 ATE: Acute Toxicity Estimate
 CAS: Chemical Abstract Services
 CSA: Canadian Standards Association
 EC50: Effective Concentration 50%
 EINECS: European Inventory of Existing Commercial chemical Substances
 ENCS: Existing and New Chemical Substances
 HSDB: Hazardous Substances Data Bank
 IARC: International Agency for Research on Cancer
 IBC: Intermediate Bulk Container
 IECSC: Inventory of Existing Chemical Substances
 IMDG: International Maritime Dangerous Goods
 IOC: Inventory of Chemicals
 KECI: Korean Existing Chemicals Inventory
 KECL: Korean Existing Chemicals List
 LC: Lethal Concentration
 LD: Lethal Dose
 N/Ap: Not Applicable
 N/Av: Not Available
 NIOSH: National Institute of Occupational Safety and Health
 NOEC: No observable effect concentration
 OECD: Organisation for Economic Co-operation and Development
 OSHA: Occupational Safety and Health Administration
 PEL: Permissible exposure limit
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
 QSAR: Quantitative structure-activity relationship
 RTECS: Registry of Toxic Effects of Chemical Substances
 SDS: Safety Data Sheet
 STEL: Short Term Exposure Limit
 TDG: Canadian Transportation of Dangerous Goods Act & Regulations
 TLV: Threshold Limit Values
 TWA: Time Weighted Average
 WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2018.
 2. International Agency for Research on Cancer Monographs, searched 2019.
 3. Canadian Centre for Occupational Health and Safety, CCIInfoWeb databases, 2019 (Chempendium, HSDB and RTECs).
 4. Material Safety Data Sheets from manufacturer.
 5. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2019.

SAFETY DATA SHEET

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

<p>Prepared for: Blaster Holdings, LLC 8500 Sweet Valley Drive Valley View, Ohio 44125 USA T (216)901-5800 (US) (800)858-6605 (Canada) Please direct all enquiries to Blaster Holdings, LLC</p>	
<p>Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Blumenthal Brands Integrated, LLC and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc., Blumenthal Brands Integrated, LLC and Blaster Holdings, LLC expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Blaster Holdings, LLC.

END OF DOCUMENT